



Sinopuren Energy Group Ltd

Moude (SL130CE-18P) Specifications

ITEM NO. :	SL130CE-18P		
Maximum Power (W)	130	120	110
Optimum Operating Voltage (Vmp)	17.57	17.57	17.57
Optimum Operating Current (Imp)	7.4	6.82	6.26
Open Circuit Voltage (Voc)	21.60	21.60	21.60
Short Circuit Current (Isc)	7.91	7.30	6.70
Solar Cell:	156*156 Poly		
Number of Cell (pcs)	4*9		
Brand Name of Solar Cells	OEM		
Size of Module (mm)	1485*669*40		
Cable & Connector Type	Pass the TUV Certificate		
Frame (Material Corners, etc.)	Aluminium-alloy		
Backing (Brand Type)	TPT		
Cell Efficiency for 280W (%)	15%		
Weight Per piece (KG)	12.5		
FF (%)	70-76%		
Junction Box Type	Pass the TUV Certificate		
Tolerance Wattage (e.g. +/-5%)	±5%		
Front Glass Thickness (mm)	3.20		
Temperature Coefficients of Isc (%) °C	+0.04		
Temperature Coefficients of Voc (%) °C	-0.38		
Temperature Coefficients of Pm (%) °C	-0.47		
Temperature Coefficients of Im (%) °C	+0.04		
Temperature Coefficients of Vm (%) °C	-0.38		
Temperature Range	-40°C to +85°C		
Surface Maximum Load Capacity	2400 Pa		
Allowable Hail Load	23m/s, 7.53g		
Bypass Diode Rating (A)	12		
Warranty	90% of 10 years, 80% of 25 years.		
Standard Test Conditions	AM1.5 1000W/ m2 25+/-2 °C		
Packing			
1*20'	20 Pallets / 486 pcs		
1*40'HQ	44 Pallets / 1012 pcs		

